

RH 9

The solution for everyday labels

At UPM Raflatac we've developed a new multipurpose hot-melt adhesive. The new RH 9 has been designed to deliver excellent performance on rough, moist and cold surfaces.

Ideal application for logistic labelling to food packaging — it is this versatility and efficiency that make RH 9 the smart adhesive choice every single day.

- Good bleed-resistance and steady matrix stripping give a clean advantage for fast conversion and better convertibility.
- Less bleed in the converting process means faster press speed and reduced machine downtime.
- Effective at a wide range of temperatures — perfect for dry and moist application.
- Available in a wide range of labelstock combinations.

For further information about service and availability, please contact our sales office.

UPM RAFLATAC



UPM RAFLATAC TECHNICAL INFORMATION

10/2011 OC 0022

ADHESIVE	RH 9
Type	General purpose strong permanent hot-melt
Use	For product labelling in applications where the surface is moist or if very high initial adhesion is required. Very good adhesion to non-polar surfaces.

Typical technical values

Tack min	17	N	FTM 9
Shear min	5.0	h	FTM 8
Labelling temperature min	2	°C	
Service temperature min	-30	°C	
Service temperature max	50	°C	
Limitations	Not suitable for labelling on plasticised PVC.		

Warranty	Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use.
----------	--

This publication replaces all previous versions. All information is subject to change without notice.

RH 9 is available in the following combinations:

- Castgloss / RH 9 / WG65
- Castgloss / RH 9 / PP30
- Raflacoat Plus / RH 9 / WG65
- Raflacoat Plus / RH 9 / PP30
- Transfer Extra / RH 9 / WG65
- Thermal Plus / RH 9 / WG65

